


# CZ 131

100 Watt max | 4  $\Omega$  |  $\varnothing$  130 mm / 5"



## COASSIALI

2 Vie coassiali, membrana woofer in cellulosa smorzata, tweeter in neodimio  
2 Way coax, doped paper cone, neodymium tweeter



Potenza nominale	<b>50 W</b>	Re	<b>3,5 <math>\Omega</math></b>	D	<b>106 mm</b>
Impedenza nominale	<b>4 <math>\Omega</math></b>	Fs	<b>119 Hz</b>	Vas	<b>3,85 dm<sup>3</sup></b>
Sensibilità (1W/1m)	<b>91 dB</b>	Qms	<b>6,05</b>	Bxl	<b>2,68 Wb/m</b>
$\varnothing$ bobina mobile	<b>25 mm</b>	Qes	<b>1,85</b>	Xmax	<b>1,1 mm</b>
Altezza traferro	<b>4 mm</b>	Qts	<b>1,41</b>	$\eta_o$	-
Fori di fissaggio	<b>4 <math>\varnothing</math> 5 / <math>\varnothing</math> 140</b>	Mms	<b>5,7 g</b>	Le	-
Foro pannello	<b>112 mm</b>	Cms	<b>0,35 mm/N</b>	Peso	<b>0,51 Kg</b>