


# CZ 140

90 Watt max | 4  $\Omega$  | ellittico 150 x 96 mm / 6"x4"



## COASSIALI

2 Vie coassiali, membrana woofer in cellulosa smorzata, tweeter in neodimio

2 Way coax, doped paper cone, neodymium tweeter



|                     |                                          |     |                                |          |                            |
|---------------------|------------------------------------------|-----|--------------------------------|----------|----------------------------|
| Potenza nominale    | <b>40 W</b>                              | Re  | <b>3,5 <math>\Omega</math></b> | D        | <b>99 mm</b>               |
| Impedenza nominale  | <b>4 <math>\Omega</math></b>             | Fs  | <b>159 Hz</b>                  | Vas      | <b>2,29 dm<sup>3</sup></b> |
| Sensibilità (1W/1m) | <b>92 dB</b>                             | Qms | <b>6,80</b>                    | Bxl      | <b>2,71 Wb/m</b>           |
| Ø bobina mobile     | <b>25 mm</b>                             | Qes | <b>1,73</b>                    | Xmax     | <b>1,1 mm</b>              |
| Altezza traferro    | <b>4 mm</b>                              | Qts | <b>1,38</b>                    | $\eta_o$ | -                          |
| Fori di fissaggio   | <b>4 <math>\varnothing</math> 73x123</b> | Mms | <b>3,63 g</b>                  | Le       | -                          |
| Foro pannello       | <b>ell. 144x87 mm</b>                    | Cms | <b>0,28 mm/N</b>               | Peso     | <b>0,48 Kg</b>             |