


# CW 162

200 Watt max | 4  $\Omega$  |  $\varnothing$  165 mm / 6,5"



## WOOFER

Membrana in cellulosa smorzata e sospensione in gomma  
Doped paper cone, rubber surround



|                             |                                                                    |     |                              |          |                          |
|-----------------------------|--------------------------------------------------------------------|-----|------------------------------|----------|--------------------------|
| Potenza nominale            | <b>90 W</b>                                                        | Re  | <b>3 <math>\Omega</math></b> | D        | <b>130 mm</b>            |
| Impedenza nominale          | <b>4 <math>\Omega</math></b>                                       | Fs  | <b>40 Hz</b>                 | Vas      | <b>26 dm<sup>3</sup></b> |
| Sensibilità (1W/1m)         | <b>91 dB</b>                                                       | Qms | <b>2,22</b>                  | BxI      | <b>7,37 Wb/m</b>         |
| $\varnothing$ bobina mobile | <b>38 mm</b>                                                       | Qes | <b>0,23</b>                  | Xmax     | <b>4,5 mm</b>            |
| Altezza traferro            | <b>6 mm</b>                                                        | Qts | <b>0,21</b>                  | $\eta_o$ | <b>0,54 %</b>            |
| Fori di fissaggio           | <b>4 <math>\varnothing</math> 5 / <math>\varnothing</math> 156</b> | Mms | <b>18 g</b>                  | Le       | <b>0,57 mH</b>           |
| Foro pannello               | <b>142 mm</b>                                                      | Cms | <b>1,06 mm/N</b>             | Peso     | <b>2,4 Kg</b>            |

